



RECONSTRUCTION CRITERIA

DESIGN SPEED > 45 MPH
 RECOVERABLE TERRAIN / CLEAR ZONE = 18' (MINIMUM)
 BORDER WIDTH = 8' (MINIMUM)
 MEDIAN PAINTED BUFFER WIDTH = 2'

NOTE:

1. TYPICAL SECTION DOES NOT COMPLY WITH HORIZONTAL CLEARANCE AND TIE DOWN DISTANCES.
2. LIMITS OF R.O.W. CANNOT BE PRESERVED WITH THIS TYPICAL SECTION SINCE SOME AREAS HAVE AN EXISTING R.O.W. OF 35' AND THE MINIMUM R.O.W. FOR THE PROPOSED TYPICAL IS $\geq 62'$.
3. SWALES SHOULD BE A MINIMUM OF 12'.
4. BIKE PATH SHOULD BE A MINIMUM OF 10'.

REVISIONS						PROJECT DEVELOPMENT & ENVIRONMENT STUDY	STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION			KROME AVENUE TYPICAL SECTION (ACTION PLAN ORIGINAL)	SHEET NO.
DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION		ROAD NO.	COUNTY	FINANCIAL PROJECT ID		
					PRELIMINARY COPY SUBJECT TO CHANGE (2-7-06)		SR-997	MIAMI-DADE	249614-4-22-01		2